



T5-2000-Series Models*

| Model No. | For Use on Cables | Range in Lbs. | Riser Used |
|-----------------|-------------------|---------------|------------|
| T5-2002-101-00 | 1/16, 3/32, 1/8 | 10 - 100 | No. 1 |
| | 5/32, 3/16 | 15 - 150 | No. 2C |
| | 7/32, 1/4 | 25 - 150 | No. 3 |
| T5-2002-103-00 | 1/16, 3/32, 1/8 | 30 - 160 | No. 1 |
| | 5/32, 3/16 | 30 - 200 | No. 2C |
| | 7/32, 1/4 | 30 - 150 | No. 3 |
| T5-2002-104-00 | 1/16, 3/32, 1/8 | 30 - 200 | No. 1 |
| | 5/32, 3/16 | 30 - 300 | No. 2C |
| | 7/32, 1/4 | 30 - 300 | No. 3 |
| T5-2002-104A-00 | 1/16, 3/32 | 30 - 300 | No. 1 |
| | 5/32, 3/16, 1/8 | 30 - 300 | No. 2C |
| | 7/32, 1/4 | 30 - 300 | No. 3 |
| T5-2002-105-00 | 1/16, 3/32, 1/8 | 30 - 200 | No. 1 |
| | 5/32, 3/16 | 30 - 400 | No. 2C |
| | 7/32, 1/4 | 30 - 400 | No. 3 |
| T5-2002-301-00 | 3, 5, 10 (CWT) | 10 - 100 | No. 1 |
| | 15, 25 (CWT) | 15 - 150 | No. 2C |
| | 35, 45 (CWT) | 25 - 150 | No. 3 |
| T5-2002-304-00 | 3, 5, 10 (CWT) | 30 - 200 | No. 1 |
| | 15, 25 (CWT) | 30 - 300 | No. 2C |
| | 35, 45 (CWT) | 30 - 300 | No. 3 |
| T5-2002-401-00 | 1/16, 3/32, 1/8 | 10 - 100 | No. 1 |
| | 5/32, 3/16 | 15 - 150 | No. 2C |
| | 7/32, 1/4 | 25 - 150 | No. 3 |
| | 10, 15 (CWT) | 10 - 100 | No. 1 |
| | 15 (CWT) | 15 - 150 | No. 2C |
| | 20, 25 (CWT) | 15 - 150 | No. 2C |
| 70 (CWT) | 25 - 150 | No. 3 | |
| T5-2004-113-00 | 1/16, 3/32, 1/8 | 10 - 100 | No. 1 |
| T5-2006-115-00 | 1/16 | 5 - 60 | No. 1 |

*RECOMMENDATION: Secondary Control Cable Tensiometer. Practice has proved that improve accuracy of readings is obtained, and the safety factor improved when the service operator is provide with two Tensiometers. One for high tensions and particularly one for secondary control systems, where low tensions predominate. Model T5-2004-113-00, with fixed risers, is the ideal instrument for use on cables using tension to 100 pounds maximum.